

MATERIAL SAFETY DATA SHEET (MSDS)

EROSION CONTROL LOG

PRODUCT AND COMPANY IDENTIFICATION

Industrial Fabrics, Inc.
510 O' Neal Lane
Baton Rouge, LA 70819
800-848-4500

GreenSolutions™ Erosion Control Log

HAZARDOUS INGREDIENTS

-----NONE-----

PHYSICAL DATA

Appearance & Odor: Straw Fiber, Extruded Plastic Mesh
Solubility in Water: Negligible
Melting Point: 285° - 300° F
Specific Gravity: Variable (Dependant on Moisture Content)
% Volatile by Volume: N/A
PH: 5

FIRE AND EXPLOSION DATA

Flash Point: > 600° F
Autoignition Temperature: >400° - 500° F
Explosive Limits in Air: N/A
Extinguishing Media: Water Spray, Dry Chemical
Special Fire Fighting Procedures: Spray with water. Wear SCBA and protective clothing to prevent contact with skin.
Unusual Fire & Explosion Hazards: Strong to Severe (if log cones in contact with ignition source)

REACTIVITY DATA

Stability: Stable
Incompatibility: Avoid contact with oxidizing agents, drying oils, flame, temperatures over 400° F
Polymerization: None
Hazardous Decomposition Products: Combustion will produce carbon dioxide, carbon monoxide, aldehydes and inorganic acids.

MATERIAL SAFETY DATA SHEET (MSDS)

EROSION CONTROL LOG

HEALTH HAZARDS

Exposure Limits: N/A

Eye Contact: No specific hazard

Skin Contact: Molten material will produce thermal burns

Ingestion: Low hazard

Inhalation: May cause nasal dryness, irritation and obstruction

EMERGENCY FIRST AID PROCEDURES

Ingestion: Remove to fresh air, get medical attention, if difficulty in breathing occurs

Eye Contact: Wash with water, if irritation develops get medical attention

Skin Contact: If burned by contact with molten material, cool quickly and get medical attention

Note to Physician: Burns should be treated as thermal burns. Plastic will come off as healing occurs.

SPILL AND LEAK PROCEDURES

Removal and Disposal: Clean up and incinerate or bury according to federal, state and local regulations

SPECIAL PRECAUTIONS

In accordance with good industrial practices, handle with care, avoid contact with oxidizing materials and provide ventilation.

Manufactured by: Industrial Fabrics – 510 O' Neal Lane – Baton Rouge, LA 70819
225-273 9600 Phone • 225-273 0440 Fax
www.greensolutions.us

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT FURNISHED HEREUNDER OTHER THAN AT THE TIME OF DELIVERY IT SHALL BE OF THE QUALITY AND SPECIFICATION STATED HEREIN. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED, AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE, ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. ANY RECOMMENDATIONS MADE BY SELLER CONCERNING THE USES OR APPLICATIONS OF SAID PRODUCT ARE BELIEVED RELIABLE AND SELLER MAKES NO WARRANTY OF RESULTS TO BE OBTAINED. IF THE PRODUCT DOES NOT MEET IFI CURRENT PUBLISHED SPECIFICATIONS AND THE CUSTOMER GIVES NOTICE TO IFI BEFORE INSTALLING THE PRODUCT, THEN IFI INC. WILL REPLACE THE PRODUCT WITHOUT CHARGE OR REFUND THE PURCHASE PRICE.