

DOUBLE NET STRAW/COCONUT - DSC 2

DSC 2 consists of 70% agricultural straw and 30% coconut fiber bound stitched on both sides by photodegradable polypropylene netting with openings of 3/8 in. x 3/8 in. DSC 2 is designed for steeper inclines and higher-flow situations. DSC 2 is considered an extended-term solution that degrades in ± 2 years.

| PROPERTY | TEST METHOD | ENGLISH | METRIC |
|-----------------------|-------------|--------------------------|--------------------------|
| Roll Size | | 8 ft X 112.5 ft | 2.4 m x 34.29 m |
| Roll Weight | | 55 lbs +/- | 25 Kg |
| Physical | | | |
| Mass / Unit Area | ASTM D 6475 | 8.8 oz / yd ² | 298.3 g / m ² |
| Thickness | ASTM D 6525 | 0.40 in | 10.2 mm |
| Mechanical | | | |
| Grab Tensile Strength | ASTM D 6818 | 100 x 100 lb / ft | 1.5 x 1.5 kN / m |
| Grab Elongation | ASTM D 6818 | 30% | 30% |
| Endurance | | | |
| Functional Longevity | Observed | Up to 24 months | Up to 24 months |

- All values are minimum average roll values unless otherwise stated.
- Longevity may vary depending on the area in which the product is installed.

Manufactured by: Industrial Fabrics – 510 O’ Neal Lane – Baton Rouge, LA 70819
 225-273 9600 Phone – 225-273 0440 Fax
www.greensolutions.us